
OWNER'S MANUAL

P/N P374-2200

1 For All[™] Programmable Digital Thermostat



- 7 Day programmable
- Pre-Programmed
- Occupied Comfort
- Unoccupied Energy Savings
- Auto Changeover
- Easy To Read Display
- Thermoglow[™] Backlight
- •*Multi-Stage, One for All
- 3 Security Levels

Meets California Title 24

* Use with most Air Conditioning & Heating Systems including: 1 or 2 Stage Electric Cooling & Gas Heating, Heat Pump, Electric or Hydronic Heat.



Commercial Systems & Services © Carrier Corporation 05/02

Table Of Contents

| | 3 5 | |
|-----------------------------------|--------|--|
| QUICK START Set the clock and go | 5 | |
| 0 | 5 | |
| BASIC OPERATION | | |
| PROGRAMMING Occupied / Unoccupied | 8 | |
| ADVANCED SETUP | | |
| ABOUT ADVANCED OPERATION 1 | 6 | |
| | | |



CAUTION


Follow Installation Instructions before proceeding.


SET THERMOSTAT TO MODE "OFF" PRIOR TO CHANGING SETTINGS IN SETUP OR RESTORING FACTORY DEFAULTS.

Commercial Systems & Services © Carrier Corporation 05/02


P/N P374-2200

Front Panel





Page 2



Page 3


Display

- 5 Override Indication Indicates the current program is currently being overridden for up to 4 hours. *Page 7,16.*
- Occupied or Unoccupied Indication
 Indicates the program number: Occupied 1,2,3, or Unoccupied. Page 8-11.
- Setup Indication Indicates the thermostat is in the programming mode. Page 12.
- Fan Operation Indication
 Fan On indicates constant, continuous fan operation.
 When Fan On is not lit indicates the fan will

only operate when necessary to heat or to cool. *Page 12.*

- Locked Indication
 Locked appears after the right combination of
 - buttons are pressed, rendering the buttons inoperative. *Page 18.*
- **Start / Stop** Indication Start or Stop appears when programming timer functions. *Page 9.*

Quick Start Set the Clock and Go



This thermostat is preprogrammed from the factory to operate 1 or 2 Stage equipment without the need for further programming. To optimize the installation of this thermostat follow the instructions in the Advanced Setup section.

* The thermostat is not preprogrammed from the factory to operate electric heat or heat pump systems. To control these systems, follow the steps in the Advanced Setup section, pages 12 & 13.

Basic Operation

Select Mode

12:00_{Pm} The HEAT setting indicates the 0 temperature the room has to heat 59 reach before the furnace will Press turn on to heat the room. 12:00 Pm The COOL setting indicates the 0 temperature the room has to reach before the air conditioner will turn on to cool the room. Press MODE 12:00_{Pm} AUTO will automatically select heat or cool based on room Αυτο temperature demand. HEAT 89 Press MODE (12:00_{Pm} Program On Program On will activate the Occupied 1 0 stored timer operation. (Occupied or HEAT 70 Unoccupied Periods) Press MODE 12:00_{Pm} **OFF** indicates both heating 0 and air conditioning OFF systems are turned off.

Basic Operation

Select Desired Temperature





Pressing the up/down buttons in \underline{Auto} mode will adjust both the heat and cool set temperatures simultaneously.

Pressing the up/down buttons in Heat <u>or</u> Cool modes will adjust only the heat **or** cool set temperature.






*⊿*7*12:00* pm


<u>.</u> М:**ЭО**Рт During programmed, unoccupied periods a press of the Override button will force the thermostat into Occupied 1 comfort settings, temporarily, for 30 minutes. Pressing the override button when the countdown timer is less than 30, will reset the timer to 30 minutes. If the timer displays 30 minutes, the next press will zero out the override timer, returning to unoccupied.

When in Override, the Override icon and the Occupied 1 icon appear on the display.


The time of day clock alternates with the time remaining in override.

During Override, the setpoints are adjustable, provided the keypad is not locked.






Page 9




Page 10




PROGRAMMING NOTES


- If only 1 Occupied period is selected in step 1 on page 8, Occupied 2 & 3 programming steps are skipped. Further, if only 2 occupieds are selected, Occupied 3 programming steps are skipped.
- Heat & Cool setpoints for Occupied 1 are the same for every day of the week. Heat & Cool setpoints for Occupied 2 & 3 can be adjusted differently for each day of the week, if desired.
- If the start time is set later in the day than the stop time, the program will run from the start time to midnight and from midnight to the stop time on the same day. For example: 9:00pm start, 8:00am stop, on Monday. In this example the program will run from 12:00am Monday to 8:00am Monday and again from 9:00pm Monday to 12:00pm Monday.
- The Unoccupied settings take effect at all times when: (1) the program is on and (2) the current time is outside a preset occupied period. For this reason start and stop times aren't necessary for unoccupied.
- \$ If the same start and stop times are programmed in for an occupied period, then it will run 24 hours.
- If one occupied period starts and stops within another occupied period the lower occupied # has priority. For example: If Occupied 3 is programmed to be "on" 24 hours, and Occupied 2 is programmed to run that day, then Occupied 2 settings will take over from occupied 3 between Occupied 2 start and stop times.



Page 12



Page 13






Advanced Setup

Advanced Setup Table

| Step # | Description | Range | Factory Default |
|--------|-------------------------------------|--------------|-----------------|
| 1 | Time of day clock set | 24 hour | 12:00 Am |
| 2 | Day of the week | Sun - Sat | Monday |
| 3 | Heat Pump | Off / On | Off |
| 4 | Reversing Valve Polarity | O/B | 0 |
| 5 | Electric Heat | Off / On | Off |
| 6 | Deadband or Temperature swing | 1 - 6 | 2 |
| 7 | Forced minimum difference heat/cool | 0 - 6 | 2 |
| 8 | Cycles per hour | d, d1, 2 - 6 | 6 |
| 9 | Thermoglow backlight | Off / On | On |
| 10 | Reset Service Filter Icon | | |
| 11 | Service Filter run time set | 0 - 1950 | 0 |
| 12 | Fahrenheit or Centigrade | F/C | F |
| 13 | Security Levels | 0 - 4 | 4 |
| 14 | Maximum allowable Heat setpoint | 35 - 99 | 80 |
| 15 | Minimum allowable Cool setpoint | 35 - 99 | 65 |


- CLOCK BACKUP In the event of a power loss, the thermostat internal clock will continue to keep proper time for a minimum of 48 hours without external power or batteries.
- 2 STAGE OPERATION The 2nd Stage of heat or cool is turned on when (1) the 1st Stage has been on for a minimum of two minutes, <u>and</u> (2) the temperature spread from the setpoint is equal to or greater than: *the setpoint plus the deadband, plus 2 degrees.*



- MINIMUM HEAT/COOL SETPOINT DIFFERENCE The Heat and Cool setpoints will not be allowed to come any closer to each other than the value set in Advanced Setup step # 7, on page 13. This minimum difference is enforced during Auto changeover and Program On operation.
- OVERRIDE As explained on *page 7*, pressing the Override button during a programmed, Unoccupied period will force the thermostat into Occupied 1, temporarily, for 30 minutes. If the Override button is pressed during an Occupied period, the thermostat will be forced into Unoccupied and the occupied # (1,2 or 3), it was forced out of will be turned off, only for that day.

During Override periods the setpoints may be adjusted, but they will not be remembered after Override ends.

- ENERGY SAVING SMART FAN If Fan On is selected, the fan will run continuously at all times, except in Off, and will only run if there is a heating or cooling demand in Unoccupied periods.
- EMERGENCY HEAT To turn on Emergency Heat press in the Fan button. While holding the Fan button press the Up button. The Cool setpoint display will read 'EH'.



During Emergency Heat the thermostat will turn on the fan and the 2nd stage of heat, when there is a demand for heat, locking out the 1st stage compressor. Exiting Emergency Heat is the same as entering. During Emergency Heat only OFF and HEAT are available. Note: Emergency Heat is only available when the thermostat is controlling a heat pump.

- ELECTRIC HEAT Selecting Electric Heat <u>on</u>, page 13, step 6, will cause the thermostat to turn on the fan immediately any time there is a heat demand. Since all gas furnaces control the fan, this feature should be off unless the heater is only electric.
- KEYPAD LOCK To prevent unauthorized use of the thermostat, the front panel buttons may be disabled. To disable, or 'lock' the keypad, press and hold in the Mode button. While holding the Mode button in, press the Up and Down buttons in together. The Locked icon will appear on the display.



To **unlock** the buttons, again press and hold the Mode button. While holding the Mode button in, press the Up and Down buttons in together. The **Locked** icon will disappear from the display.

DUAL SETPOINT BEHAVIOR - The adjustable setpoint range is: 35 - 99 degrees in Fahrenheit and 7 - 35 degrees in Centigrade. When in the modes Heat or Cool, this adjustable range is unhampered.

When adjusting any Auto mode, including programming Occupied and Unoccupied periods, the thermostat will not allow the Heat setpoint to get closer to the Cool setpoint than the value programmed as the minimum difference in *step 7, page 13.*

When entering the Auto mode from Cool, the Heat and Cool setpoints will remain spread apart by the amount that they were adjusted, prior to entering Auto. For example: If the Cool setpoint was set to 80 while in the Cool mode and the Heat setpoint was adjusted to 70 while in the Heat mode, upon entering the Auto mode the Heat and Cool setpoints would be 80 and 70. <u>Both</u> setpoints would then move up and down together, (in this example spread by 10 degrees), by pressing the up or down buttons.

To move the Heat and Cool setpoints closer together, enter the Cool or Heat mode by pressing the Mode button, then adjust the setpoint(s) closer together. <u>Heat</u> is limited to how close it can come to Cool by *step 7, page 13*. The above applies if the Security level does not equal 4.

FACTORY DEFAULTS - If, for any reason it is desirable to return all stored settings back to the factory default settings, press the Mode button. While holding the Mode button in, press the Fan button for 5 sec. All icons will appear. Press and hold in the Fan button until Fd appears. This resets all factory settings. To return to normal operation, press the Mode button twice more.

Warranty

One-Year Warranty - This Product is warranted to be free from defects in material and workmanship. If it appears within one year from the date of original installation, whether or not actual use begins on that date, that the product does not meet this warranty, a new or remanufactured part, at the manufacturer's sole option, to replace any defective part will be provided without charge for the part itself; PROVIDED the defective part is returned to the distributor through a qualified servicing dealer.

THIS WARRANTY DOES NOT INCLUDE LABOR OR OTHER COSTS incurred for diagnosing, repairing, removing, installing, shipping, servicing or handling of either defective parts or replacement parts. Such costs may be covered by a separate warranty provided by the installer.

THIS WARRANTY APPLIES ONLY TO PRODUCTS IN THEIR ORIGINAL INSTALLATION LOCATION AND BECOMES VOID UPON REINSTALLATION.

LIMITATIONS OF WARRANTIES – ALL IMPLIED WARRANTIES (INCLUDING IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MERCHANTABILITY) ARE HEREBY LIMITED IN DURATION TOT THE PERIOD FOR WHICH THE LIMITED WARRANTY IS GIVEN. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE MAY NOT APPLY TO YOU. THE EXPRESSED WARRANTIES MADE IN THIS WARRANTY ARE EXCLUSIVE AND MANY NOT BE ALTERED, ENLARGED, OR CHANGED BY ANY DISTRIBUTOR, DEALER, OR OTHER PERSON WHATSOEVER.

ALL WORK UNDER THE TERMS OF THIS WARRANTY SHALL BE PERFORMED DURING NORMAL WORKING HOURS. AL REPLACEMENT PARTS, WHETHER NEW OR REMANUFACTURED, ASSUME AS THEIR WARRANTY PERIOD ONLY THE REMAINING TIME PERIOD OF THIS WARRANTY.

THE MANUFACTURER WILL NOT BE RESPONSIBLE FOR:

- Normal maintenance as outlined in the installation and servicing instructions or owners manual including filter cleaning and/or replacement and lubrication.
- Damage or repairs required as a consequence of faulty installation, misapplication, abuse, improper servicing, unauthorized alteration or improper operation.
- Failure to start due to voltage conditions, blown fuses, open circuit breakers or other damages due to the inadequacy or interruption of electrical service.
 Damage as a result of floods, winds, fires, lightning, accidents, corrosive environments or
- Damage as a result of floods, winds, fires, lightning, accidents, corrosive environments o other conditions beyond the control of the Manufacturer.
- Parts not supplied or designated by the Manufacturer, or damages resulting from their use.
 Manufacturer products installed outside the continental U.S.A., Alaska, Hawaii, and
- Canada. 7. Electricity or fuel costs or increases in electricity or fuel costs from any reason whatsoever
- including additional or unusual use of supplemental electric heat.
 ANY SPECIAL INDIRECT OR CONSEQUENTIAL PROPERTY OR COMMERCIAL DAMAGE OF ANY NATURE WHATSOEVER. Some states do not allow the exclusion of
 - incidental or consequential damages, so the above may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which may vary form state to state.